



Harris 1324-40

Dimensions

Width:	Height:	Depth	Seat Width:	Seat Height:	Seat Depth:	Arm Height:	Weight:
70"	38"	36"	60"	20"	21"	25"	300lbs

Description: Harris Full Sleeper

COM Yardage: 11.75 RR Yards -or- 12.5 Yards NR

Seat Cushion Style: Loose reversible, Nylon Zipper closure in casings.

Seat Cushion Content: Standard Seat Cushion: 1.8 High Resilient foam core, wrapped in two layers of plush foam and one layer of fiber.

Back Cushion Style: Semi-Attached, Nylon Zipper Closure in casings.

Back Cushion Content: Fiber filled back with 7 Denier Siliconized fiber enclosed in a channeled muslin casing.

Back Cushion Support: Inter-weave 3" nylon webbing covered with heavy duty batting materials. Provides uniform support and superior life.

Frame: Frame stocks are harvested from certified sustainable sources. All stress joints to be connected utilizing one of the following, Double Doweled, screwed and glued - corner block, glued and Heavy Duty Frame Staples. Glue is polyvinyl acetate.

Front Leg Height: 5.50" -Front Legs Removable Y Back Leg Height: 5.50" -Back Leg Removable: Y

Finish: Durable Catalyzed finish, HAPS free (Hazardous Air Pollutants), UV inhibitor, and resistant to cleaning chemicals.

Mechanism: Heavy duty contract mechanism Leggett & Platt "Classic Square". One-piece, heavy gauge steel construction featuring properly spaced cross-members for sleeping comfort and stability. Anti-tilt safety feature keeps the unit in contact with the floor at all times in the open position.

Mattress: Heavy duty contract mattress 5.25" 13.5 gauge Verticoil edge with Active support technology innerspring mattress Hypoallergenic pad exhibits strength and durability CFR 1632.

Warranty: Frame and Springs - 10 years Sleeper Mechanism - 5 years Mattress Standard, Princess & Linen 312 - 3 year Cushions: Standard -2 years; Comfort Firm & Pocketed Coil - 3 years.

Upholstered furniture pieces with overall widths of 48" or greater using Non-Railroad fabrics may require additional seaming. Railroad fabrics are recommended for these pieces. This product is manufactured to comply with the state of California standards for flammability as specified in the Technical Bulletin 117-2013, and NFPA260