



## Michelina 1669-05

Dimensions							
Width:	Height:	Depth	Seat Width:	Seat Height:	Seat Depth:	Arm Height:	Weight:
26"	36"	31"	18"	19"	23"	23"	60lbs

**Description:** Michelina Chair With Nails

**COM Yardage:** 4.50 RR Yards -or- 4.50 Yards NR

**Seat Cushion Style:** Loose reversible, Nylon Zipper closure in casings.

**Seat Cushion Content:** 1.8 High Resilient foam core, wrapped in two layers of plush foam and one layer of fiber.

**Seat Cushion Support:** Inter-weave 3" nylon webbing covered with heavy duty batting materials. Provides uniform seat foam support and superior seat deck life.

**Back Cushion Style:** Tight

**Back Cushion Content:** 1.5 density High Resilient Polyurethane foam with fiber overlay.

**Back Cushion Support:** Coated sheet webbing applied to the rails. Provides uniform support and superior life.

**Frame:** Frame stocks are harvested from certified sustainable sources. All stress joints to be connected utilizing one of the following, Double Doweled, screwed and glued - corner block, glued and Heavy Duty Frame Staples. Glue is polyvinyl acetate.

**Front Leg Height:** 7.50" -Front Legs Removable N **Back Leg Height:** 6.50" -Back Leg Removable: N

**Finish:** Durable Catalyzed finish, HAPS free (Hazardous Air Pollutants), UV inhibitor, and resistant to cleaning chemicals.

**Warranty:** Frame and Springs - 10 years Cushions : Standard-2 years; Comfort Firm & Pocketed Coil - 3 years; Tight seat - 2 years.

**Restrictions:** Style Is Restricted To No Match Patterns. Random Or Solid Fabrics Only.

**Additional Notes:** Style Is Restricted To No Match Patterns. Random Or Solid Fabrics Only. Wrinkling Is An Inherent Characteristic And Will Vary Depending On Fabric Content.

Upholstered furniture pieces with overall widths of 48" or greater using Non-Railroad fabrics may require additional seaming. Railroad fabrics are recommended for these pieces. This product is manufactured to comply with the state of California standards for flammability as specified in the Technical Bulletin 117-2013, and NFPA260