



## Bowie 1982-20

### Dimensions

Width:	Height:	Depth	Seat Width:	Seat Height:	Seat Depth:	Arm Height:	Weight:
50.50"	35"	36.75"	46"	20"	19"	23"	

### Description: Bowie Loveseat

COM Yardage: 4.5 RR Yards -or- 4.75 Yards NR

Seat Cushion Style: Loose reversible, Nylon Zipper closure in casings, attached with Velcro

Seat Cushion Content: 2.3 High Resilient foam core, wrapped in two layers of plush foam and encased in a moisture resistant barrier. All cushions and padding materials meet UFAC & California Technical Bulletin 117.

Seat Cushion Support: Wood Slats

Back Cushion Style: Loose reversible, Nylon Zipper closure in casings, attached with D rings.

Back Cushion Content: 1.5 density High Resilient foam core encased in fiber.

Back Cushion Support: Wooden Slats

Frame: Frame stocks are harvested from certified sustainable sources. All stress joints to be connected utilizing one of the following, Double Doweled, screwed and glued - corner block, glued and Heavy Duty Frame Staples. Glue is polyvinyl acetate.

Front Leg Height: 0" -Front Legs Removable N Back Leg Height: 0" -Back Leg Removable: N

Finish: Frames finished in 14 step process utilizing a catalyzed conversion varnish sealer and top coat. Conversion varnish offers superior moisture resistance, cleaner / chemical resistance and surface strength. The coating includes a UV Inhibitor.

Warranty: Kellex warrants exposed wood-framed seating against defects in materials and workmanship, under conditions of normal use and service, for 6 years from the date of purchase. (Casters â€" 2 years.)

Upholstered furniture pieces with overall widths of 48" or greater using Non-Railroad fabrics may require additional seaming. Railroad fabrics are recommended for these pieces. This product is manufactured to comply with the state of California standards for flammability as specified in the Technical Bulletin 117-2013, and NFPA260