



Stockton ER13507-LM

Dimensions

Width:	Height:	Depth	Seat Width:	Seat Height:	Seat Depth:	Arm Height:	Weight:
24.50"	30.50"	24"	19"	18"	21"	24.50"	70lbs

Description: Stockton Metal Base Ergonomic Chair

COM Yardage: 2.5 RR Yards -or- 2.75 Yards NR

Seat Cushion Style: Tight

Seat Cushion Content: 1.8 density High Resilient Foam with fiber overlay.

Seat Cushion Support: Contoured plywood with breather holes.

Back Cushion Style: Tight

Back Cushion Content: 1.5 density High Resilient foam with fiber overlay.

Back Cushion Support: Contoured plywood with breather holes.

Frame: 9 ply solid birch plywood with gas cylinder for adjustable height, includes swivel and tilt mechanism.

Warranty: Kellex warrants Ergonomic Chairs against defects in materials and workmanship, under conditions of normal use and service, for 5 years from the date of purchase. (Knee Tilt and Gas Lift mechanisms 2 years; casters 2 years.) Kellex does not accept responsibility for any damages to desks, tables, etc. caused by chairs pushed into or underneath them.

Additional Notes: 3" Gas Cylinder Adjusts The Min Seat Height To 18" And The Max Seat Height To 21" (Overall Min Height To 30.5" And Overall Max Height To 33.5").

Upholstered furniture pieces with overall widths of 48" or greater using Non-Railroad fabrics may require additional seaming. Railroad fabrics are recommended for these pieces. This product is manufactured to comply with the state of California standards for flammability as specified in the Technical Bulletin 117-2013, and NFPA260