



Dudley HC09585-30

Dimensions

| Width: | Height: | Depth | Seat Width: | Seat Height: | Seat Depth: | Arm Height: | Weight: |
|--------|---------|--------|-------------|--------------|-------------|-------------|---------|
| 82.50" | 36" | 32.50" | 72.50" | 20" | 20.50" | 25" | |

Description: Dudley Sofa

COM Yardage: 10.5 RR Yards -or- 12 Yards NR

Seat Cushion Style: Loose reversible, Nylon Zipper closure in casings.

Seat Cushion Content: 2.3 High Resilient foam core, wrapped in two layers of plush foam and encased in a moisture resistant barrier.

Seat Cushion Support: Glass-fiber reinforced plastic slats

Back Cushion Style: Loose reversible, Nylon Zipper closure in casings.

Back Cushion Content: 1.5 density High Resilient foam core encased in fiber.

Back Cushion Support: Inter-weave 3" nylon webbing covered with heavy duty batting materials. Provides uniform support and superior life.

Frame: Frame stocks are harvested from certified sustainable sources. All stress joints to be connected utilizing one of the following, Double Doweled, screwed and glued - corner block, glued and Heavy Duty Frame Staples. Glue is polyvinyl acetate.

Front Leg Height: 9.25" -Front Legs Removable N Back Leg Height: 9.25" -Back Leg Removable: N

Finish: Frames finished in 14 step process utilizing a catalyzed conversion varnish sealer and top coat. Conversion varnish offers superior moisture resistance, cleaner / chemical resistance and surface strength. The coating includes a UV Inhibitor.

Warranty: Frame and Springs - 10 years Cushions : Standard-2 years; Comfort Firm & Pocketed Coil - 3 years; Tight seat - 2 years.

Restrictions: Not Available With Optional Removeable Seat Or Clean Out.

Additional Notes: Not Available With A Removeable Seat Deck Or Clean Out.

Upholstered furniture pieces with overall widths of 48" or greater using Non-Railroad fabrics may require additional seaming. Railroad fabrics are recommended for these pieces. This product is manufactured to comply with the state of California standards for flammability as specified in the Technical Bulletin 117-2013, and NFPA260