



Shiloh HC09661-15

Dimensions							
Width:	Height:	Depth	Seat Width:	Seat Height:	Seat Depth:	Arm Height:	Weight:
54"	24.50"	25.50"	45.50"	20"	25.50"	24.50"	85lbs

Description: Shiloh Bench

COM Yardage: 3.25 RR Yards -or- 3.25 Yards NR

Seat Cushion Style: Tight

Seat Cushion Content: 2.3 density High Resilient foam, with crown patch and fiber overlay.

Seat Cushion Support: 8 gauge 60% post consumer recycled sinuous steel springs spaced 5" apart, inter spring connected with tie wires. Spring system to be secured with additional hardwood stabilizer front rail and covered with heavy duty batting and seat denim.

Frame: Frame stocks are harvested from certified sustainable sources. All stress joints to be connected utilizing one of the following, Double Doweled, screwed and glued - corner block, glued and Heavy Duty Frame Staples. Glue is polyvinyl acetate.

Front Leg Height: 10.50" -Front Legs Removable Y **Back Leg Height:** 10.50" -Back Leg Removable: Y

Finish: Frames finished in 14 step process utilizing a catalyzed conversion varnish sealer and top coat. Conversion varnish offers superior moisture resistance, cleaner / chemical resistance and surface strength. The coating includes a UV Inhibitor.

Warranty: Frame and Springs - 10 years Cushions : Standard-2 years; Comfort Firm & Pocketed Coil - 3 years; Tight seat - 2 years.

Upholstered furniture pieces with overall widths of 48" or greater using Non-Railroad fabrics may require additional seaming. Railroad fabrics are recommended for these pieces. This product is manufactured to comply with the state of California standards for flammability as specified in the Technical Bulletin 117-2013, and NFPA260