



Hitchcock HC09703-09

Dimensions

Width:	Height:	Depth	Seat Width:	Seat Height:	Seat Depth:	Arm Height:	Weight:
33.75"	43.50"	36"	23"	20.50"	20.50"	25.50"	

Description: Hitchcock Recliner

Seat Cushion Style: Loose reversible, Nylon Zipper closure in casings.

Seat Cushion Content: 2.3 High Resilient foam core, wrapped in two layers of plush foam and encased in a moisture resistant barrier.

Seat Cushion Support: Steel seat box, 8 gauge sinuous steel springs secured with insulated self lubricating clips and innerspring connected with steel tie wires. Spring support system covered in heavy duting batting. Also has a steel Chassis for a rigid and dependable frame.

Back Cushion Style: Tight

Back Cushion Content: 1.2 density High Resilient foam core encased in fiber

Back Cushion Support: 10-12 Gauge 60% post consumer recycled sinuous steel springs, inter spring connected with tie wires, covered with heavy duty batting.

Frame: Frame stocks are harvested from certified sustainable sources. All stress joints to be connected utilizing one of the following, Double Doweled, screwed and glued - corner block, glued and Heavy Duty Frame Staples. Glue is polyvinyl acetate.

Front Leg Height: 5.50" -Front Legs Removable Back Leg Height: 5.50" -Back Leg Removable:

Finish: Durable Catalyzed finish, HAPS free (Hazardous Air Pollutants), UV inhibitor, and resistant to cleaning chemicals.

Warranty: Frame and Springs - 5 years, Recliner/ Glider/Swivel Mechanism- 1 year, Cushions : Standard-2 years; Comfort Firm & Pocketed Coil - 3 years; Tight seat - 2 years.

Additional Notes: Glide Options Not Available For This Style. Reclined Length Is 71" With A 17" Wall Clearance Needed. Recliner Mechanism Opens By Pushing Against The Arms And Back When In A Seated Position. Power Mechanisms Available With Rechargeable Battery Pack For Additional Charge. Required Carton Included.

Upholstered furniture pieces with overall widths of 48" or greater using Non-Railroad fabrics may require additional seaming. Railroad fabrics are recommended for these pieces. This product is manufactured to comply with the state of California standards for flammability as specified in the Technical Bulletin 117-2013, and NFPA260