



Zola HC09738-30CO

Dimensions

Width:	Height:	Depth:	Seat Width:	Seat Height:	Seat Depth:	Arm Height:	Weight:
69"	34.50"	31.50"	63"	19.50"	19.50"	25"	200lbs

Description: Zola Sofa With Clean Out

COM Yardage: 6.75 RR Yards -or- 8.25 Yards NR

Seat Cushion Style: Tight

Seat Cushion Content: 2.3 density High Resilient foam, with crown patch and fiber overlay.

Seat Cushion Support: 8 gauge 60% post consumer recycled sinuous steel springs spaced 5" apart, inter spring connected with tie wires. Spring system to be secured with additional hardwood stabilizer front rail and covered with heavy duty batting and seat denim.

Back Cushion Style: Tight

Back Cushion Content: 1.5 density High Resilient foam with fiber overlay.

Back Cushion Support: Inter-weave 3" nylon webbing covered with heavy duty batting materials. Provides uniform support and superior life.

Frame: Frame stocks are harvested from certified sustainable sources. All stress joints to be connected utilizing one of the following, Double Doweled, screwed and glued - corner block, glued and Heavy Duty Frame Staples. Glue is polyvinyl acetate.

Front Leg Height: 6" -Front Legs Removable Y Back Leg Height: 6" -Back Leg Removable: Y

Finish: Durable Catalyzed finish, HAPS free (Hazardous Air Pollutants), UV inhibitor, and resistant to cleaning chemicals.

Warranty: Frame and Springs - 10 years Cushions : Standard-2 years; Comfort Firm & Pocketed Coil - 3 years; Tight seat - 2 years.

Restrictions: Style Is Restricted To Non-Matched Patterns. Random Or Solid Fabrics Only. All Non-Railroad Fabrics Will Require Additional Seaming .

Additional Notes: Style Is Restricted To Non-Matched Patterns. Random Or Solid Fabrics Only. All Non-Railroad Fabrics Will Require Additional Seaming.

Upholstered furniture pieces with overall widths of 48" or greater using Non-Railroad fabrics may require additional seaming. Railroad fabrics are recommended for these pieces. This product is manufactured to comply with the state of California standards for flammability as specified in the Technical Bulletin 117-2013, and NFPA260